

(12) **United States Patent**
Piepenburg

(10) **Patent No.:** **US 8,309,014 B2**
(45) **Date of Patent:** **Nov. 13, 2012**

(54) **METHOD OF TRIMMING UNFIRED POTTERY USING A TURNABLE APPARATUS**

(76) Inventor: **Robert E. Piepenburg**, Ann Arbor, MI (US)

(* Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 654 days.

(21) Appl. No.: **12/604,807**

(22) Filed: **Oct. 23, 2009**

(65) **Prior Publication Data**

US 2010/0044906 A1 Feb. 25, 2010

Related U.S. Application Data

(62) Division of application No. 11/824,377, filed on Jun. 29, 2007, now abandoned.

(60) Provisional application No. 60/831,758, filed on Jul. 19, 2006.

(51) **Int. Cl.**
B28B 11/08 (2006.01)

(52) **U.S. Cl.** **264/680**; 264/310; 264/312; 264/632; 264/633; 264/679

(58) **Field of Classification Search** 264/310, 264/312, 632, 633, 679, 680; 425/266, 267, 425/268, 459, 400

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,409,257 A 7/1921 Staley
1,551,728 A * 9/1925 Burger 425/265
1,732,339 A * 10/1929 Osborne 425/263

1,751,049 A * 3/1930 Miller 425/214
2,370,410 A * 2/1945 Miller 264/679
2,450,437 A * 10/1948 Miller 264/312
2,465,450 A 3/1949 Hawk
2,599,910 A * 6/1952 Guthrie 425/267
2,638,653 A * 5/1953 Adams 425/86
2,813,324 A 11/1957 Watkin
2,876,522 A 3/1959 Johnson
3,386,140 A * 6/1968 Bruckner 425/3
3,387,347 A 6/1968 John
3,520,036 A * 7/1970 Maloney 425/90
3,605,218 A * 9/1971 Rasmussen et al. 425/459
3,778,212 A 12/1973 Takahashi
3,796,105 A 3/1974 Menard
3,894,830 A 7/1975 Edwards
4,028,041 A 6/1977 Zambrano, Jr.

(Continued)

FOREIGN PATENT DOCUMENTS

JP 1-244804 A 9/1989

Primary Examiner — Joseph S. Del Sole


Assistant Examiner — Seyed Masoud Malekzadeh

(74) *Attorney, Agent, or Firm* — Carrier Blackman & Associates, P.C.; William D. Blackman; Joseph P. Carrier

(57) **ABSTRACT**

A rotatable turntable tool is used in trimming wheel-thrown pottery. The turntable tool includes a base portion, a bearing member, and a cap portion which is rotatably attached to the base portion. A method of trimming an unfired clay workpiece includes steps of inverting the workpiece and placing it at a central portion of a wheel head on a potter's wheel; placing the turntable tool on top of a central portion of the inverted workpiece; pressing downwardly on the cap portion of the turntable tool while rotating said wheel head to stabilize the workpiece, whereby the base portion of the turntable tool rotates with the workpiece, while the cap portion is substantially restrained from rotating; and applying a trimming tool to an edge of the workpiece to remove unwanted clay therefrom.

17 Claims, 7 Drawing Sheets



US 8,309,014 B2

Page 2

U.S. PATENT DOCUMENTS								
				5,783,123	A *	7/1998	Edwards et al.	264/39
4,057,384	A *	11/1977	Reid	6,419,319	B1	7/2002	Sakurai	
4,102,622	A	7/1978	Simpson	7,195,474	B1	3/2007	Summers	
4,222,577	A	9/1980	Giffin	7,200,895	B2	4/2007	Dayt	
4,332,542	A	6/1982	Matsui	7,261,543	B2	8/2007	Lester	
4,368,021	A	1/1983	Ryckman	7,504,064	B2	3/2009	Jo	
4,503,943	A	3/1985	Tsukui	7,641,464	B2 *	1/2010	Griffin et al.	425/267
4,585,240	A *	4/1986	Giffin	2003/0215538	A1	11/2003	Oakes	
4,689,001	A	8/1987	Yoder	2004/0025850	A1	2/2004	Hiraiwa et al.	
4,702,920	A	10/1987	Goodman	2004/0033284	A1	2/2004	Adachi et al.	
4,806,090	A	2/1989	Finlay	2004/0142061	A1	7/2004	Oakes	
4,857,256	A	8/1989	Fujii et al.	2005/0025850	A1	2/2005	D'Estais	
5,047,194	A	9/1991	Roufs et al.	2005/0108851	A1	5/2005	Dayt	
5,230,909	A	7/1993	Stanly	2006/0016060	A1 *	1/2006	Lester	29/428
5,244,376	A	9/1993	Meyers	2008/0203613	A1	8/2008	Jo	
5,479,867	A	1/1996	Blevins et al.	2008/0258336	A1	10/2008	Lester	
5,695,703	A *	12/1997	Craven et al.					

* cited by examiner

FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3A





FIG. 3B






FIG. 3C

FIG. 4




FIG. 5




FIG. 6





FIG. 7



**METHOD OF TRIMMING UNFIRED
POTTERY USING A TURNABLE
APPARATUS**

CROSS-REFERENCE TO RELATED
APPLICATIONS

The present invention is a divisional of U.S. patent application Ser. No. 11/824,377, filed on 29 Jun. 2007. The present application claims priority under 35 USC 119(e) based on U.S. provisional patent application No. 60/831,758 filed on Jul. 19, 2006. The subject matter of each of the referenced priority documents, including claims, specification and drawings, is incorporated by reference herein.

BACKGROUND OF THE INVENTION

1. Field of the invention

The present invention relates to a method of trimming unfired pottery, using a turntable tool. The tool includes a base which spins with a pottery workpiece, and a cap member operatively attached to the base and adapted to rotate relative to the base.

2. Description of the Background Art

It has been a common practice in trimming pottery for an artisan to invert a wheel-thrown workpiece on a rotatable wheel head of a potter's wheel, when the workpiece has partially dried to a stage referred to in the art as "leather hard"; to center the workpiece on the wheel head; and to press downwardly on the inverted base of the workpiece during trimming. It has also been known to place an inverted metal lid in the center of the base of the workpiece during a trimming operation on unfired pottery. This lid may be, for example, a lid from a baby food jar. Then, the artisan places a finger in the center of the lid and applies a light downward pressure to the workpiece, through the lid, while the wheel spins at an appropriate trimming speed, and this stabilizes the workpiece on the wheel head and distributes the finger pressure, while the artisan trims away unwanted superfluous clay from the exterior and base of the workpiece.

Using this type of inverted lid, however, does not entirely avoid the occurrence of friction between the spinning lid and the user's fingertip. Such friction may generate heat and be uncomfortable for the user.

Many different designs for turntables have been patented, for a number of different applications. Examples of some of the known turntables include U.S. Pat. No. 1,409,257 (Staley), U.S. Pat. No. 1,732,113 (Van Der Meer), U.S. Pat. No. 4,117,627 (Slingerland, Jr.), U.S. Pat. No. 4,549,714 (Busch), U.S. Pat. No. 5,479,867 (Blevins et al.), U.S. Pat. No. 5,779,309 (Lu), and U.S. Pat. No. 5,783,123 (Edwards et al.)

Although the known turntables have some utility for their intended purposes, a need still exists in the art for an improved tool for use in trimming unfired clay pots, and to an improved method of trimming unfired clay pots using such a turntable tool. In particular, there is a need for an improved trimming tool which will overcome the difficulties encountered with the known art, and which will speed up the trimming process.

SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide an improved method and turntable tool for use in stabilizing an unfired clay workpiece during a trimming operation thereon, in an intermediate stage of manufacture.

A turntable apparatus according to an illustrative embodiment includes a base member, a bearing member which fits

into an opening in the base member, and a cap member including a dependent central post which fits into a hole in the center of the bearing.

The base member may be textured on a bottom surface thereof, to better grip the clay surface of a workpiece during use. The base member may further have a plurality of open cutouts formed in the lower surface thereof, and may also have a plurality of radial ribs on the underside thereof extending between the cutouts.

The bearing member may be a bearing, such as a sealed bearing, or alternatively, may be an annular bushing. Where a bushing is used, it may be formed from sintered plastic or metal, impregnated with a lubricant.

The cap member includes a relatively thin upper disc, which may have a shallow recess formed centrally therein to receive a fingertip of a user. The cap member also includes a post attached to and extending downwardly from the upper disc, where the post is dimensioned and configured to fit into the central hole of the bearing member.

The diameter of the upper disc may be in a range between 3 cm and 7 cm.

For a more complete understanding of the present invention, the reader is referred to the following detailed description section, which should be read in conjunction with the accompanying drawings. Throughout the following detailed description and in the drawings, like numbers refer to like parts.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an exploded perspective view of a turntable tool according to a first illustrative embodiment of the present invention;

FIG. 2A is a top plan view of the turntable tool of FIG. 1; FIG. 2B is a partial side plan view and a partial sectional view of the turntable tool of FIG. 1;

FIG. 2C is a bottom plan view of the turntable tool of FIG. 1;

FIG. 3A is an environmental perspective view of a first step in a trimming process according to the present invention, showing an inverted clay workpiece centered on a wheel head;

FIG. 3B is an environmental perspective view of a second step in the trimming process according to the present invention, showing a turntable tool according to the invention centered on an inverted workpiece;

FIG. 3C is an environmental perspective view of a third step in the trimming process according to the present invention, showing finger pressure being applied downwardly on the turntable tool while a user removes unwanted clay from the base of the workpiece using a conventional metal trimming tool;

FIG. 4 is a schematic diagram showing a sequence of steps in an illustrative method according to the present invention;

FIG. 5 is a perspective view of a turntable tool according to a second illustrative embodiment of the present invention;

FIG. 6 is a cross-sectional view of the turntable tool of FIG. 5, taken along the line 6-6; and

FIG. 7 is an exploded lower perspective view of the turntable tool of FIGS. 5-6.

DETAILED DESCRIPTION

The present invention provides an improved turntable tool, and method of using the disclosed tool to stabilize an unfired clay workpiece during a trimming operation thereon, in an intermediate stage of manufacturing the workpiece.

3

Referring now to the drawings, a turntable apparatus according to a first illustrative embodiment of the invention is shown generally at **10** in FIG. 1, in exploded perspective view. The turntable apparatus **10** includes a base member **12**, a bearing member **16**, and a cap member **20**. Each of these components will be discussed in further detail below.

In the first embodiment of the turntable apparatus **10**, the base member **12** is formed generally in the shape of a flattened cylinder with a hollow cylindrical recess **14** formed centrally therein, to receive the bearing member **16**. The base member **12** includes a substantially smooth and unbroken side wall **15** extending therearound. Also in the first depicted embodiment, the base member **12** includes a closed floor portion **35** extending across a lower surface **30** thereof at the bottom of the recess **14**, sealing the recess **14** from contact by water or other environmental elements below the tool. The base member **12** may be formed of a slightly resilient plastic material, so as to be non-brittle.

The base member **12** may be knurled, or otherwise may be textured, on a lower surface **30** thereof. The lower surface **30** of the base member **12** may have a plurality of open cutouts **32** (FIG. 2B, 2C) formed therein to create such a textured surface. The lower surface **30** may also have a plurality of radial ribs **34** thereon extending between the cutouts **32**, as shown in FIG. 2C.

The bearing member **16** is generally annular in shape, with a hollow central hole **18** formed centrally therein to receive a post **22** of the cap member **20**. The bearing member **16** is configured and dimensioned to fit snugly inside of the recess **14** of the base member **12**, with a slight interference fit to retain the bearing member therein. The bearing member **16** may be a multi-component bearing assembly, such as a sealed ball bearing or roller bearing. Alternatively, the bearing member **16** may be an annular bushing. Where a bushing is used, it may be formed from sintered plastic or metal, and optionally, may be impregnated with a wax or with another lubricant. However, the relatively low speed at which the cap member **20** is expected to rotate, in relation to the base **12**, makes the use of a lubricant optional.

The cap member **20** includes a relatively thin upper disc **21**, which may have a shallow recess **25** formed centrally therein to receive a fingertip of a user. The diameter of the upper disc **21** may be in a range between 3 cm and 7 cm. The cap member **20** also includes a cylindrical post **22**, integrally attached to and extending downwardly from the upper disc. The post **22** is dimensioned and configured to fit into the central hole **14** of the bearing member, and to suspend the upper disc **21** slightly above, and spaced away from the base member **12**, so as to avoid direct contact therebetween. This spacing provides a narrow gap between the upper disc **21** and the base member.

Referring now to FIGS. 5-7, a turntable apparatus according to a second illustrative embodiment of the invention is shown generally at **110** in FIG. 5, and this same apparatus is shown in cross-section in FIG. 6, and in exploded perspective view in FIG. 7. The turntable apparatus **110** in this second embodiment includes a base member **112**, a bearing subassembly **116**, and a cap member **120**. Each of these components will be discussed in further detail below.

In the turntable apparatus **110** according to the second embodiment, the base member **112** is formed generally in the shape of a flattened cylinder with a hollow cylindrical open space **114** formed therein, to receive the bearing subassembly **116**. The base member **112** includes a substantially smooth and unbroken side wall **115** extending therearound, with an upper lip flange **113** extending substantially horizontally outwardly at the top of the side wall **115**, as shown. The upper lip flange **113** is provided for cooperating with a lower lip flange

4

121 of the cap member **120**, to retain the cap member on the base member through an interference fit between the upper lip flange **113** and the lower lip flange **121**.

Also in the second embodiment, the base member **112** includes a closed floor portion **135** extending across a lower surface **130** thereof at the bottom of the recess **114**, sealing the recess from contact by water or other environmental elements below the turntable tool. The base member **112** may be formed of a slightly resilient plastic material such as polyethylene or another suitable polymer, so as to be non-brittle.

The base member **112** may be knurled, or otherwise may be textured, on the lower surface **130** thereof, as shown in FIG. 7.

The bearing subassembly **116** includes a perforated ring member **125** which is generally annular in shape, and which may have a hollow central hole **118** formed centrally therein. The perforated ring member **125** has a number of evenly-spaced collars **126** formed therein, including hollow apertures in each of the collars to retentively receive ball bearings **127**. The bearing subassembly **116** is configured and dimensioned to fit loosely inside of the recess **114** of the base member **112**. The bearing subassembly **116** may be a multi-component bearing assembly, as shown. Alternatively, the bearing subassembly **116** may be replaced with a sealed bearing assembly or by an annular bushing. Where a bushing is used, it may be formed from sintered plastic or metal, and optionally, may be impregnated with a wax or with another lubricant. However, the relatively low speed at which the cap member **120** is expected to rotate, in relation to the base **112**, makes the use of a lubricant optional.

The cap member **120** includes a relatively thin upper disc **123**, which may have a shallow recess **124** formed centrally therein to receive a fingertip of a user. The width, or diameter of the upper disc **123** may be in a range between 3 cm and 7 cm.

The cap member **120** also includes an integral side wall **122**, integrally attached to and extending downwardly from an outer edge portion of the upper disc **123**. The side wall **122** of the cap member **120** is dimensioned and configured to fit outside of side wall **115** of the base member **112**, and the bearing subassembly **116** suspends the upper disc **123** slightly above, and spaced away from the base member **112**, so as to avoid direct contact therebetween. This spacing provides a narrow gap between the upper disc **123** and the base member **112**.

Referring now to FIGS. 3A-3C and 4, an illustrative method of trimming an unfired clay workpiece, using the turntable tool **10** or **110**, will now be described.

Those in the relevant art will understand that immediately after a clay workpiece has been hand-formed on a potter's wheel **36** (FIG. 3A), the workpiece is quite soft and malleable, and is generally too soft to undergo an immediate trimming operation. Therefore, the workpiece is air-dried for a period of time, until it is partially dried to an intermediate state known in the art as "leather hard", whereupon it can withstand the forces exerted thereon in a trimming operation. This drying operation can take place overnight in a "wet box", or the workpiece may be allowed to sit out uncovered to dry immediately after it is formed, where the user is available to wait for the partial drying process to take place.

Once the workpiece **38** has attained a leather-hard condition, it is inverted and placed at the center of a rotatable wheel head **37** of a potter's wheel **36**, with the base **40** of the workpiece oriented facing upwardly. The base **40** includes a rough, uneven outer edge portion **42** in need of trimming. This step of the method is depicted in FIG. 3A, and is also shown at **50** in the method flowchart of FIG. 4.

5

Once the workpiece **38** has been centered on the wheel head **37**, the turntable tool **10** or **110** is then placed on a central portion of the inverted workpiece base **40**, with the cap portion of the tool facing upwardly. This step of the method is depicted in FIG. 3B, and is shown at **52** in the method flowchart of FIG. 4.

After the turntable tool **10** or **110** has been centered on the base **40** of the workpiece **38**, the user then presses downwardly on the turntable tool to stabilize the workpiece, while rotating the wheel head at an appropriate trimming speed. A selected fingertip of the user fits engagingly into the recess **25** in the top of the cap portion **20** during this step. The base portion **12** of the turntable tool rotates with the workpiece **38** and spins about the stationary post **22** of the cap portion **20**, while the cap portion **20** remains substantially still. This step of the method is depicted in FIG. 3C, and is shown at **54** in the method flowchart of FIG. 4.

In the next step of the method hereof, a trimming tool **44** is applied to the rough edge **42** of the workpiece **38**, to remove unwanted clay **45** therefrom. This step of the method is also depicted in FIG. 3C, and is shown at **56** in the method flowchart of FIG. 4.

Optionally, the trimming tool may then be removed, and additional clay may be removed from a central portion of the base.

After the trimming operation has been completed, the workpiece is allowed to dry completely over a period of days until it reaches a "bone-dry" condition, after which it is vitrified in a conventional firing process in a kiln. This may be a two-stage process in which a glaze is applied to the finished workpiece after an initial bisque firing, and the glaze is then melted in a final, high-temperature firing.

Although the present invention has been described herein with respect to a number of specific illustrative embodiments, the foregoing description is intended to illustrate, rather than to limit the invention. Those skilled in the art will realize that many modifications of the preferred embodiment could be made which would be operable. All such modifications, which are within the scope of the claims, are intended to be within the scope and spirit of the present invention.

Having, thus, described the invention, what is claimed is:

1. A method of trimming a clay workpiece, comprising the steps of:

- a) inverting the workpiece and placing it at a central portion of a wheel head on a potter's wheel;
- b) placing a turntable tool on top of a central portion of the inverted workpiece, said turntable tool comprising a base member and a cap member rotatably attached to said base member, wherein the base member and the cap member are configured to permit rotatable movement of the base member relative to the cap member;
- c) pressing downwardly on the cap member of the turntable tool while rotating said wheel head to stabilize the workpiece, whereby the base member of the turntable tool rotates with the workpiece, while the cap member is substantially restrained from rotating; and
- d) applying a trimming tool to an edge of the workpiece to remove unwanted clay therefrom.

2. The method of claim **1**, wherein the turntable tool comprises:

- said base member having a central opening formed therein;
- a bearing which fits in the central opening of the base member and which has a central hole formed therein;
- and

6

said cap member comprising an upper disc, and a post attached to and extending downwardly from the upper disc, the post dimensioned and configured to fit into the central hole of the bearing.

3. The method of claim **2**, wherein the upper disc has a diameter in a range between 3 and 7 centimeters.

4. The method of claim **2**, wherein the upper disc has a shallow recess formed centrally therein to receive a fingertip of a user, and wherein the step of pressing downwardly comprises pressing into the shallow recess of the upper disc.

5. The method of claim **2**, wherein the base member is textured on a bottom surface thereof, and wherein the textured bottom surface of the base member frictionally engages a surface of the inverted workpiece.

6. The method of claim **2**, wherein the base member has a plurality of open cutouts formed in a lower surface thereof.

7. The method of claim **6**, wherein the lower disc has a plurality of radial ribs on an underside thereof extending between said cutouts.

8. A method of trimming a clay workpiece, comprising the steps of:

- a) inverting the workpiece and placing it at a central portion of a wheel head on a potter's wheel;
- b) placing a turntable tool on a central portion of the inverted workpiece, said turntable tool comprising:
 - a base member having a central opening formed therein;
 - a bearing which fits in the central opening of the base member and which has a central hole formed therein;
 - and
 - a cap member comprising an upper disc, and a post attached to and extending downwardly from the upper disc, the post dimensioned and configured to fit into the central hole of the bearing, wherein the base member is rotatably movable relative to the cap member;
- c) pressing downwardly on the turntable tool while rotating said wheel head to stabilize the workpiece, whereby the base portion of the turntable tool rotates with the workpiece, while the cap portion is substantially restrained from rotating; and
- d) applying a trimming tool to an edge of the workpiece to remove unwanted clay therefrom.

9. The method of claim **8**, wherein the upper disc has a diameter in a range between 3 and 7 centimeters.

10. The method of claim **8**, wherein the upper disc has a shallow recess formed centrally therein to receive a fingertip of a user, and wherein the step of pressing downwardly comprises pressing into the shallow recess of the upper disc.

11. The method of claim **8**, wherein the base member is textured on a bottom surface thereof, and wherein the textured bottom surface of the base member frictionally engages a surface of the inverted workpiece.

12. The method of claim **8**, wherein the base member has a plurality of open cutouts formed in a lower surface thereof.

13. The method of claim **12**, wherein the lower disc has a plurality of radial ribs on an underside thereof extending between said cutouts.

14. A method of trimming a clay workpiece, comprising the steps of:

- a) inverting the workpiece and placing it at a central portion of a wheel head on a potter's wheel;
- b) placing a turntable tool on a central portion of the inverted workpiece, said turntable tool comprising:
 - a base member having a central opening formed therein, wherein the base member is textured on a bottom surface thereof, and wherein the textured bottom surface of the base member frictionally engages the inverted workpiece;

7

- a bearing which fits in the central opening of the base member and which has a central hole formed therein; and
- a cap member comprising an upper disc having a shallow recess formed centrally therein to receive a fingertip of a user, and a post attached to and extending downwardly from the upper disc, the post dimensioned and configured to fit into the central hole of the bearing, wherein the base member is rotatably movable relative to the cap member;
- c) pressing downwardly on the turntable tool by pressing into the shallow recess of the upper disc while rotating said wheel head to stabilize the workpiece, whereby the

8

- base portion of the turntable tool rotates with the workpiece, while the cap portion substantially restrained from rotating; and
- d) applying a trimming tool to an edge of the workpiece to remove unwanted clay therefrom.
- 5 **15.** The method of claim **14**, wherein the upper disc has a diameter in a range between 3 and 7 centimeters.
- 16.** The method of claim **14**, wherein the base member has a plurality of open cutouts formed in a lower surface thereof.
- 10 **17.** The method of claim **16**, wherein the lower disc has a plurality of radial ribs on an underside thereof extending between said cutouts.

* * * * *